



CARE . TRUST . RESPONSIBILITY

# RP-100-300 II Receipt Printer



## High Speed Receipt Printer

### RP-100-300 II Printer Special Features

- ESC/POS & STAR command sets compatible
- Direct thermal line and 203 dpi
- Interface: Serial +USB +Ethernet
- Built-in WebConfig page, make ethernet setting easy to use through IE
- Support two-dimensional bar code printing function
- Standard GB18030 simplified / traditional Chinese characters library
- Built-in large data buffer to process printing data
- Characters can be enlarged, bold, underlined; character line spacing can be adjusted
- Support different density bitmap and graphics printing
- Support network printing status monitoring
- Windows driver, Linux driver, OPOS driver available

# High Speed Receipt Printer-RP-100-300 II

Partner Tech's receipt printers are high speed receipt printer solutions for retail and hospitality that require fast and quiet printing.

The RP-100-300 II is a particularly fast receipt printer with a printing rate up to 300 mm/s at a resolution of 203 dpi. The compact size and integrated wall mounting make this dependable model absolutely ideal for many applications. A wide range of I/O port options allows easy installation and simple integration to various POS solutions.

Item	RP-100-300 II	
Printing	Print method	Direct thermal line
	Print width	72-64mm
	Dot density	576-512dot/line
	Resolution	203dpi
	Print speed	300mm/s
	Interface	Serial+Ethernet+USB
	Paper diameter	83mm
	Paper width	80mm
	Line space	3.75mm(can be adjusted)
	Sensor	Paper End, Cover Open, Paper Cut
	Character Size	ANK Font Font A: 12x24dots Font B: 9x17dots Simplified/Traditional Chinese Character: 24x24dots
	Code page	PC437/Katakana/PC850/PC860/PC863/PC865/ West Europe/Greek/Hebrew/East Europe/Iran/ WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/ PT151,1251/PC737/WPC1257/Thai Vietnam/PC864/ PC1001
	Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ ITF/CODABAR/CODE93/CODE128/QRCODE
Fonts support	English, Simple Chinese, Traditional Chinese, Korean, Japanese	
Buffer	Data	128K bytes
	NV Flash	256K bytes
Power	Cashdrawer out	DC 24V/1A
	Power supply	AC 110V/220V , 50 ~ 60Hz , DC 12V/3A
Physical properties	Weight	1.25kg
	Dimension	180*139*128mm
Environment	Work environment	Temperature:5-45°C , Humidity:10 ~ 80%
	Storage environment	Temperature:-10 ~ 50°C , Humidity:10 ~ 90%
Reliability	Tph life	150km
	Auto cutter	1 million cuts
Cutter Method	Partial cut (Guillotine)	
Certification	CE, FCC, CB	



High Speed  
Receipt Printer



Stylish Black Color



Reliable and  
Easy-to-Use



Multiple I/O for  
various connection  
options

\* specification subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

## Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX: +886-2-29153405	E-mail:sales@partner.com.tw
USA	TEL:+1-949-598-1888	FAX: +1-949-598-0088	E-mail:sales@partnertechcorp.com
Europe	TEL:+49 (0)40 450 635-0	FAX:+49 (0)40 450 635-130	E-mail:info@partner-tech.eu
UK	TEL:+44 (0)1928 579 707	FAX:+44 (0)1928 571 308	E-mail:sales@partnertechuk.com
China	TEL:+86-21-67696667	FAX: +86-21-67696699	E-mail:sales@partnertech.com.cn
Africa	TEL:+27-11-700-7188	FAX:+27-11-700-7140	E-mail:sales@partnertech.co.za
Middle East	TEL:+971-4-8862980	FAX:+971-4-8862980	E-mail:sales@partnertechme.com
Korea	TEL:+82-10-6404-8223	I-Phone:+82-70-4104-8223	E-mail:adams_c@partner.com.tw

