



CARE . TRUST . RESPONSIBILITY

# RP-330 Receipt Printer



## High Performance Receipt Printer RP-330 Printer Features

The high speed thermal printer solution for retail and hospitality environment that require fast and quiet printing.

- Roll thermal paper
- 80mm paper width
- 200 mm/sec high speed printing
- Support full & partial cut
- Wall mounting
- Water proof cover (Option)

# High Performance Receipt Printer-RP-330

Partner Tech's thermal printers are high speed thermal printer solution for retail and hospitality environment that require fast and quiet printing. Supporting a full range of fonts for different countries.

The RP-330 is a particularly fast thermal receipt printer with a printing rate of up to 200 mm/s at a resolution of 180 dpi. The compact size and integrated wall mounting make this dependable model absolutely ideal for many applications. A wide range of interface and port options allows easy installation and simple integration to either POS environments or POS solutions.

A special feature is that the RP-330 is equipped with a signal tone that can be remotely controlled, making it the ideal printer for kitchen use.

Item		RP-330	RP-330-S	RP-330-L
Printing	Method	Thermal line printing		
	Speed	200mm/sec		
	Width	72.2mm(512Dots/Line)		
	Resolution	180DPI		
Paper	Type	Thermal Paper		
	Width	58mm~82.5mm		
	Thickness	0.06mm ~ 0.09mm		
	Roll Diameter	Maximum 80mm		
	Roll Core Inner	12mm		
Reliability	Tph life	160Km		
	Mcbf	60,000,000 Lines		
Auto cutter		1,500,000 cuts(Guillotine)		
Sensor	Standard	Paper End, Cover Open, Paper Near End		
	Option	Black Mark Sensor		
Interface	Standard	24V power jack +Cash draw +USB (B type)	24V power jack +Cash drawer +USB (B type) +Serial (RS-232C)	24V power jack +Cash drawer +USB (B type) +Serial (RS-232C) +Ethernet
	Option	Serial (RS-232C), Parallel (IEEE1284), Ethernet	N/A	N/A
Emulation		ESC/POS Command Compatible		
Driver		Window Printer Driver(8.1, 7, XP), Linux, OPOS, JavaPOS		
Power	AC	100 ~ 240VAC 50/60 Hz		
	DC	DC 24V ± 10% / 1.75A		
Temperature	Operation	5 C ~ 40 C		
	Storage	-20 C ~60 C		
Dimension		198mm x 152mm x 151mm (W x D x H)		
Color		Black		



Freedom in Placement



Design for harsh Environment-difficult for foreign objects or liquids to get inside



58-80mm Paper width



Interchangeable Serial



Interchangeable Ethernet



Interchangeable Paralle

\* specification subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

## Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX: +886-2-29153405	E-mail:sales@partner.com.tw
USA	TEL:+1-949-598-1888	FAX: +1-949-598-0088	E-mail:sales@partnertechcorp.com
Europe	TEL:+49 (0)40 450 635-0	FAX: +49 (0)40 450 635-130	E-mail:info@partner-tech.eu
UK	TEL:+44 (0)1928 579 707	FAX: +44 (0)1928 571 308	E-mail:sales@partnertechuk.com
China	TEL:+86-21-67696667	FAX: +86-21-67696699	E-mail:sales@partnertech.com.cn
Africa	TEL:+27-11-700-7188	FAX:+27-11-700-7140	E-mail:sales@partnertech.co.za
Middle East	TEL:+971-4-8862980	FAX:+971-4-8862980	E-mail:sales@partnertechme.com
Korea	TEL:+82-10-6404-8223	I-Phone:+82-70-4104-8223	E-mail:adams_c@partner.com.tw

