

NLS-HR3280-BT

Wireless 2D Barcode Scanner



Features

■ Outstanding Performance

Equipped with a outstanding CPU, this CPU-based scanner can effortlessly capture high-density, high-volume and distorted barcodes printed on paper or displayed on screen.

■ Reliable and Stable Wireless Communication

Adopting the latest Bluetooth which is strong anti-interference and stable to transmit the data.

■ Powerful Data Editing Function

The NLS-HR3280-BT allows to customize decoding mode flexibly through preset.

■ Low Consumption and Great Compatibility

The low consumption of NLS-HR3280-BT reduces connection issues and maximizes the compatibility for diverse applications.

■ Humanized Illumination Designation

The NLS-HR3280-BT can be set white and red led according to different workplaces. Not only relieving the visual fatigue but also improving working efficiency.

Application Scenarios

Retail chains, inventory management, warehouse and logistics, express delivery services and supermarket, food traceability, electricity meter reading, asset counting, healthcare, etc.

NLS-HR3280-BT

SCANNING MADE SIMPLE

Wireless 2D Barcode Scanner

Performance	Image Sensor	1280×800 CMOS	
	Illumination	White LED & Red LED	
	Aiming	Green LED	
	Symbologies	2D	PDF417, Micro PDF417, QR Code, Micro QR Code, Aztec, Data Matrix, Chinese Sensible Code, Maxicode.
		1D	EAN-8, EAN-13, UPC-E, UPC-A, Code128, Coupon, UCC/EAN128, CodaBar, I2Of5, Febraban, ITF14, ITF6, Matrix 25, Code39, Code93, ISSN, ISBN, Industrial 25, Standard 25, China Post 25, Plessey, Code 11, MSI Plessey, UCC/EAN Composite, GS1 Databar, Code 49, Code 16K, AIM 128, ISBT 128.
	Resolution*	≥3mil	
	Typical Depth of Field*	EAN-13 (13mil)	50mm-495mm
		Code 39 (5mil)	85mm-220mm
		PDF 417 (6.7mil)	70mm-215mm
		Data Matrix (10mil)	50mm-220mm
		QR Code (15mil)	20mm-325mm
	Motion Tolerance	Max. 50 cm/s/19.7 in/s	
	Scan Angle**	Pitch	±55°
Skew		±55°	
Tilt		360°	
Field of View	Horizontal 39°, Vertical 24°		
Min. Symbol Contrast	≥25%		
Wireless	Communication Mode	Synchronous, asynchronous and batch modes	
	Radio Technology	Bluetooth 5.0	
	Communication Distance	≥50m/164ft (direct line of sight in open air)	
	Memory Capacity	≥15000 pieces Code 128 (20 byte of each Code 128)	
	Battery	2200 mAh lithium-ion battery	
	Expected Charge Time	≤4 hours (with power adapter)	
	Expected Battery Life	≥12 hours of continuous operation (scan once per 6 seconds)	
	Physical	Interfaces	RS-232, USB
Dimensions		Scanner: 113.5(W)×73.3(D)×159.0(H)mm	
Weight		Scanner: 217g	
Notification		Beep, LED indicator	
Operating Voltage		5VDC±5%	
Environmental		Operating Temperature	-20°C to 60°C (-4°F to 140°F)
		Storage Temperature	-40°C to 70°C (-40°F to 158°F)
	Battery Charge Temperature	0°C to 45°C (32°F to 113°F)	
	Humidity	5% ~ 95% (non-condensing)	

Newland China
+86-591-83978605
contact@nlscan.com
www.newlandaidc.com

Newland Europe
+31(0)-345-87-0033
info@newland-id.com
www.newland-id.com

Newland North America
+1-510-490-3888
info@newlandna.com
www.newlandamerica.com

Newland Latin America
+1-239-598-0068
info@newlandla.com
www.newlandamerica.com

Newland Taiwan
+886-2-7731-5388
info@newland-id.com.tw
www.newland-id.com.tw

Newland Korea
+82-10-8990-4838
th.sung@newland-id.com.tw
www.newlandaidc.com

NLS-HR3280-BT

SCANNING MADE SIMPLE

Wireless 2D Barcode Scanner

Environmental	ESD	±8 KV (air discharge); ±4 KV (direct discharge)
	Drop	Scanner: 1.2m/3.9ft Cradle: 1m/3.3ft
	Sealing	Scanner: IP42
Certifications		FCC Part15 Class B, CE EMC Class B

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;
2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

*Specification are subject to change without notice

Version: V1.1

Newland China

+86-591-83978605
contact@nlscan.com
www.newlandaidc.com

Newland Europe

+31(0)-345-87-0033
info@newland-id.com
www.newland-id.com

Newland North America

+1-510-490-3888
info@newlandna.com
www.newlandamerica.com

Newland Latin America

+1-239-598-0068
info@newlandla.com
www.newlandamerica.com

Newland Taiwan

+886-2-7731-5388
info@newland-id.com.tw
www.newland-id.com.tw

Newland Korea

+82-10-8990-4838
th.sung@newland-id.com.tw
www.newlandaidc.com

